

# Billerud Pure Supreme™

LINER  
Imperial Units

## Product Description

Pure Supreme™ is a fully coated premium white top kraftliner suitable for offset printing and litho-laminated packaging. High strength ensures light, strong packages with minimised washboarding.  
Pure Supreme™ is produced from 100% virgin fibres.

## Basis weight

36, 41, 47 lb/1000 ft<sup>2</sup>

## Approvals

Pure Supreme™ is produced in compliance with FDA and BfR packaging norms.

## Certification

Production is certified in accordance with ISO 9001, ISO 14001, ISO 50001 and FSSC 22000.

Property	Unit					Method
Basis weight	lb/1000 ft <sup>2</sup>		36	41	47	ISO 536
Caliper	PT		8,7	10,2	12,2	ISO 534
Scott Bond	1/1000 ft.lb/in <sup>2</sup>		95	95	95	TAPPI T569
SCT	CD	lbf/in	22,3	25,1	28,0	ISO 9895
Tensile Stiffness	MD	lbf/in	7990	8905	9130	ISO 1924
	CD	lbf/in	3995	4570	4570	
Bending Resistance Taber 15°	MD	gcm	39	64	103	ISO 2493
	CD	gcm	17	27	49	
Roughness PPS-10	PS	Microns	1,6	1,6	1,6	ISO 8791-4
Gloss	PS	%	47	47	47	TAPPI T480
Brightness	PS	%	80	80	80	ISO 2470
Whiteness D65	PS	%	84	84	84	ISO 11475
Cobb	PS	lb/1000ft <sup>2</sup>	6,6	6,6	6,6	ISO 535
	RS	lb/1000ft <sup>2</sup>	8,2	8,2	8,2	
Moisture	%		7,0	7,0	7,0	ISO 287

MD = Machine Direction    CD = Cross Direction    PS = Print Side    RS = Reverse Side    Test climate: 50% RH, 23°C

The table shows typical data for a range of grammages.

Rev. 202401